

Dual Channel VHF Wireless Microphone System



LX-2020 G2 Specification

TECHNICAL FEATURE OF THE 2-IN-1 BASE MODULE

Frequency Range: VHF 216~270 MHz; Frequency Stability: +/-0.005%
 Image Interfere Rate: >80dB
 S/N Ratio: >105dB (1KHz)
 Sensitivity: -107dBm
 Audio Output Impedance: 600Ω
 Audio Output Level: -12dB
 Audio Output Level: Unbalanced Out: 0~+/-400mV, Balanced Out: 0~+/-200mV
 Power Supply: DC 12.5~18V/200mA, AC 120V
 Receiver Dimensions (WxHxD): 8.7 x 1.6 x 5.1 (inches) / 22 x 4 x 13 (cm)
 Package Dimensions (WxHxD): 15 x 11.8 x 2.4 (inches) / 38 x 30 x 6 (cm)
 Shipping Weight: 3 lbs / 1.4 kg

TECHNICAL FEATURE OF THE MICROPHONE

Frequency Preparation: PLL
 Frequency Stability: +/-0.005%
 Image Interfere Rate: >102dB
 Frequency Response: 30Hz~18kHz
 S/N Ratio: <-60dB
 RF Output: 10mW
 Current: <100mA
 Battery Voltage: 2 x AA 1.5V Alkaline Battery
 Continuous Using: 8 Hours (GP) 2 x AA 1.5V Battery
 Microphone Dimensions (WxH): 9.5 x 2.2 (inches) / 24 x 5.5 (cm)

