



**NISSINDO** GET TO THE POINT

# The Excellent & Professional Power Amplifier 2000 Watts



## MA-1330 Specifications

Rated Power (Stereo): 1320W (8 ohms) / 2000W (4 ohms)  
 Rated Power (Parallel mono): 660W (8 ohms) / 1000W (4 ohms)  
 Rated Power (Bridge): 1330W (16 ohms) / 2000W (8 ohms)  
 THD: <0.05% (10% Rated Power)  
 Intermodulation Distortion: <0.1% (60Hz/7KHz, 10% Rated Power)  
 Frequency Response (+0/-0.25dB): 20Hz-20kHz  
 Damping Factor: >800 @ 8ohm/100Hz  
 Segregation: >75dB  
 S/N Ratio (A Weight): >108dB  
 Total Gain: 37.3+/-0.5dB  
 Difference of Channel Gain: <0.25dB  
 Input Sensitivity: 1V  
 Input Impedance: Unbalanced input 10K Ohms, Balanced input 20K Ohms  
 Input Connectors: 3 pin XLR / 6.35mm

Output Connectors: Speakon binding post, NL4 Speakon  
 Cooling: 4 x fans, Stepless Shifting, Cooling airflow from front to back  
 Controls on Front Panel: Switch of AC, Gain controlling knob for channel A and B  
 Controls on Rear Panel: Parallel/Stereo/Bridge, LF cutting, Grounding, Limit  
 Indicator on Front Panel: Yellow-Bridge, Red-Overload, Green-Signal  
 Amplifier Protection: Short Circuit, Maladjustment of DC, Overload, Overheat  
 Environment Temperature: Working temperature: -10°C~40°C, Storing temperature: -25°C~80°C  
 Power Supply: AC 120V 60Hz, 1000VA  
 Dimensions (WxHxD): 19x3.5x14.8 inches / 48.3x8.8x37.5 cm  
 Packing Dimensions (WxHxD): 20.6x5x17.5 inches / 52.3x12.8x44.4 cm  
 Net Weight: 39.7 Lbs / 18 Kg  
 Shipping Weight: 44.1 Lbs / 20 Kg

